

09/25/00
JC915 U.S. PTO

9/26/00

Patent
100-1120

A

Assistant Commissioner of Patents
Box Patent Application
Washington, DC 20231

JC682 U.S. PTO
09/669313

09/25/00

Transmitted herewith is the U.S. Patent Application of
Inventor: Gustav M. Stromback
For: Reinforcing Ridge Apparatus and Method

The following checked items are enclosed:

<u>X</u>	Stamped, Self Addressed Postcard to be Returned
<u>X</u>	Check for \$345.00
<u>X</u>	Declaration and Power of Attorney
<u>12</u>	Pages of Specification Including Abstract
<u>20</u>	Total Number of Claims
<u>2</u>	Independent Claims
<u>2</u>	Sheets of Drawings
<u>X</u>	Verified Statement Claiming Small Entity Status

If there is any additional fee due, please charge such additional fee to Deposit Account No. 19-1453 (Our File No. 100-1120).

The filing fee was calculated as follows:

Basic Fee ----- \$345.00

Total Fee ----- \$345.00

Respectfully submitted,

SHAFFER & CULBERTSON, L.L.P.

Dated: 25 SEP 00

By: J. Nevin Shaffer, Jr.

J. Nevin Shaffer, Jr., Reg. No. 29,858
Russell D. Culbertson, Reg. No. 32,124
Rafael V. Baca, Reg. No. 44,016
Attorneys for Applicant
Building One, Suite 360
1250 Capital of Texas Hwy. S.
Austin, TX 78746
(512) 327-8932

"Express Mail" Mailing label number EL533564374US

Date of Deposit: September 25, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Services "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Applications, Washington, DC 20231

Reg. No. 29,858, J. Nevin Shaffer, Jr.

\\C:\db\c-h\Hemming2\100\application.transmittal.wpd

Applicant or Patentee: Gustav M. Stromback
Serial or Patent No.: Unknown
Filed or Issued: Herewith
For: REINFORCING RIDGE APPARATUS AND METHOD

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
37 C.F.R. §1.9(f) and §1.27(b) - INDEPENDENT INVENTOR

As the below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 C.F.R. §1.9(c) for the purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled REINFORCING RIDGE APPARATUS AND METHOD described in

X the specification filed herewith

___ application serial no. _____, filed _____

___ patent no. _____, issued _____

I have not assigned, granted, conveyed, or licensed and am under no obligation, under contract or law, to assign, grant, convey, or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 C.F.R. §1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 C.F.R. §1.9(d) or a nonprofit organization under 37 C.F.R. §1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

X no such person, concern, or organization.


___ persons, concerns or organizations listed below.*

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 C.F.R. §1.27)

Full Name _____
Address _____
___ Individual ___ Small Business Concern ___ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 C.F.R. §1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.


Gustav M. Stromback, Inventor

25 SEP '00
Date

REINFORCING RIDGE APPARATUS AND METHOD

INVENTOR:


GUSTAV M. STROMBACK

"Express Mail" Mailing label number EL533564374US

Date of Deposit: September 25, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Services "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Applications, Washington, DC 20231

Reg. No. 29,858, J. Nevin Shaffer, Jr.

A handwritten signature in black ink, appearing to read "J. Nevin Shaffer, Jr.", is written over a horizontal line.

REINFORCING RIDGE APPARATUS AND METHOD

BACKGROUND OF THE INVENTION

This invention relates to an improved reinforcing ridge for structural construction materials. In particular, this invention relates to a reinforcing ridge formed in a length of rigid material with first and second unjoined edges.

The difficulties of building structures out of man-made materials are many. A major difficulty is making the material rigid enough to resist compression, torsion and bending. In the field of metal housing, for example, lengths of sheet metal are formed into rectangular beams of various lengths and subsequently joined together. The prior art metal beams, when formed into rectangular shapes, dealt with the unjoined edges in one of two ways. Sometimes the unjoined edges were left unjoined so that open space existed. This is an inexpensive way to form a metal beam. Unfortunately, beams formed in this manner are not structurally strong in that they are easily deformed. The second way that the prior art handles the unjoined edges is to screw or weld them together. This results in a much more structurally sound man-made beam but dramatically increases the cost.

Additionally, either of the prior art solutions to the problem of the unjoined edges results in a man-made beam that is difficult and time-consuming, and therefore costly, to join with other beams. Currently, man-made materials such as these are joined together by screws and bolts individually attached in a labor-intensive manner. Thus, there is a need in the art for providing a reinforcing ridge in rigid material that not only deals with the problem of satisfactorily joining the unjoined edges but also results in a man-made structure that supports the use of automatic joining devices, such as pneumatic guns and screws. It, therefore, is an object of this invention

1 to provide an improved reinforcing ridge system in man-made materials, such as metal tubing, that
2 simply and inexpensively joins the unjoined edges without the use of screws and simultaneously
3 results in a structure that supports the use of automatic joining devices.
4

5 SHORT STATEMENT OF THE INVENTION

6 Accordingly, in a length of rigid material with first and second unjoined edges, the
7 reinforcing ridge of the present invention includes a short extension connected to the first unjoined
8 edge. A long extension is connected to the second unjoined edge. A connection locking slot is
9 formed in the long extension and conformed to just receive and retain the short section when the
10 unjoined edges are brought together. In a further embodiment of the invention, the short and long
11 extensions have front and back faces. The long extension front face, in this embodiment, is
12 conformed to cover the short extension front face and partially cover the short extension back face.

13 In a further embodiment, the rigid material is formed into a rectangle with the reinforcing
14 ridge in one side and at least one reinforcing rib in a side facing the reinforcing ridge. In a still
15 further embodiment, the invention includes at least one reinforcing rib in a side facing the
16 reinforcing ridge and at least one strength indent in a side adjacent to the reinforcing ridge. Other
17 preferred embodiments include two reinforcing ribs; two strength indents; two pairs of strength
18 indents; and combinations thereof.

19 A method of joining two unjoined edges in a length of rigid material is also disclosed. In
20 a preferred embodiment, the method includes forming a short extension in the first unjoined edge
21 and a long extension in the second unjoined edge. Thereafter the first and second unjoined edges
22 are brought together and the long extension is bent over the short extension forming a connection

locking slot so that the first and second unjoined edges are joined together and form a reinforcing ridge. Other embodiments of the method of the invention include forming at least one reinforcing rib in a side facing the reinforcing ridge. Additional preferred embodiments include providing at least one strength indent in a side adjacent to the reinforcing ridge. Additional methods disclose preferred embodiments of various combinations of the reinforcing ridge and reinforcing ribs and strength indents.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will become more fully apparent from the following detailed description of the preferred embodiments, the appended claims and the accompanying drawings in which:

FIGURE 1 is a side section view of a preferred embodiment of the reinforcing ridge of the present invention;

FIGURE 2 is a side section view of a preferred embodiment with two reinforcing ribs and two strength indents; and

FIGURE 3 is a side section view of a preferred embodiment of the present invention with two reinforcing ribs and two pairs of strength indents.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments of the present invention are illustrated by way of example in FIGURES 1-3. With specific reference to FIGURE 1, the reinforcing ridge 10 of the present invention includes a length of rigid material 12. Length of rigid material 12 has a short extension

1 14 connected to a first unjoined edge 16. Length of rigid material 12 further includes long
2 extension 18 connected to second unjoined edge 20. As illustrated in FIGURE 1, long extension
3 18 is first brought into contact with short extension 14 in an extended position as illustrated by the
4 dotted broken lines. Thereafter, long extension 18, in a preferred embodiment, is bent over short
5 extension 14 and forms a connection locking slot 22 into and within which the short extension 14
6 is retained. Connection locking slot 22 obviously may be made before joining edges 16 and 20.
7 In such a case, connection locking slot 22 may be formed to just accept short extension 14 so that
8 short extension 14 is forced to fit into, and is held by, locking slot 22. Obviously in either case
9 locking slot 22 may be further compressed or crimped to ensure a tighter connection if desired.

10 Reinforcing ridge 10 simply and inexpensively joins unjoined edge 16 with unjoined edge
11 20 without the need of welding, screws, bolts or the like. An important resulting advantage from
12 reinforcing ridge 10 is that, as illustrated in FIGURE 1, an automatic joining device such as a
13 pneumatic gun shooting nails 24, for example, can be utilized without collapsing rigid material 12.
14 FIGURE 1 shows nail 24 as having been shot through two sides, 23 and 25, of rigid material 12.
15 Obviously, the usual intended purpose is to join rigid material 12, as illustrated in FIGURE 1,
16 with another section of rigid material 12, not shown. Assuming the second section of rigid
17 material 12 also includes reinforcing ridge 10, the results are the same. That is, the sides, 23 and
18 25, of rigid material 12 are reinforced by reinforcing ridge 10 so as to resist collapse and enable
19 use of an automatic joining device. Obviously the advantage of the invention are not limited to
20 the use of a nail gun but also easily accommodate other automatic joining methods such as screws,
21 for example.

1 FIGURE 1 also illustrates another preferred embodiment of the invention. In this
2 embodiment, at least one reinforcing rib 26 is formed in a side, 27, opposite the reinforcing ridge
3 10. FIGURE 1 shows a pair of reinforcing ribs 26 formed in the corners of the side 27 opposite
4 the reinforcing ridge 10. The applicant has found that reinforcing ribs 26 also enhance the ability
5 of the invention to resist collapse and thereby further facilitate the use of automatic joining
6 devices.

7 In the field of construction with the use of man-made materials, a common material is sheet
8 metal. FIGURE 1 shows a length of rigid material 12, such as sheet metal, formed into a
9 rectangular shape with four sides, 23, 25, 27, and 29. Obviously, as further illustrated hereafter,
10 any appropriate building shape may be adapted to the invention including but not limited to
11 triangular and round shapes for example.

12 Referring now to FIGURE 2, another preferred embodiment of the present invention is
13 illustrated. In this embodiment, length of rigid material 12 is formed into an extended rectangular
14 shape. The rectangular shape shown in FIGURE 2 includes reinforcing ridge 10 and a pair of
15 reinforcing ribs 26. Additionally, however, FIGURE 2 includes at least one strength indent 28
16 in side 23 and/or side 25. Applicant has determined that the use of one or more strength indents
17 28 further prevents collapse of the rigid material when used with automatic joining devices and
18 enables the material to resist compression and twisting moments.

19 Referring now to FIGURE 3, another preferred embodiment of the present invention is
20 illustrated. In this embodiment, the length of rigid material 12 is again formed into an extended
21 rectangular shape. The rectangular shape shown in FIGURE 3 includes reinforcing ridge 10, at
22 least one reinforcing rib 26 and two pairs of strength indents 28. As with FIGURE 2, FIGURE

1 3 shows that strength indents 28 are located in a side, 23 or 25, adjacent to reinforcing ridge 10.
2 That is, strength indents 28 are located between reinforcing ridge 10 and reinforcing ribs 26 on
3 the joining sides of the rectangle.

4 A major problem with prior art metal construction forms, again, is that in either the open
5 unjoined condition or the welded condition, they are subject to collapse and more costly to
6 produce. Applicant's metal forms are stronger and may be joined together by automatic devices,
7 such as pneumatic guns so that 20 to 30 percent less metal is used in building a structure. Further,
8 the combination of at least one reinforcing rib 26 and/or at least one strength indent 28 in
9 combination with the reinforcing ridge 10 of the present invention results in a significantly
10 stronger metal form. This is true no matter what gauge material is used, i.e. 16, 18, and 20 gauge
11 or the like. In the construction industry for example, the construction of a truss includes tension
12 web and compression web members. Applicant's invention results in a rigid web member which
13 is much better able to resist compression. Therefore, Applicant's invention results in a reduction
14 of the number of compression web members required in the construction of a truss.

15 Referring again to FIGURE 1, the structure of the invention is reviewed with some
16 additional detail. It should be appreciated that short extension 14 and long extension 18 have a
17 front face 30 and a back face 32. When first unjoined edge 18 is brought next to second unjoined
18 edge 20 the front face 30 of long extension 18 generally covers the front face 30 of short section
19 14. As shown in FIGURE 1, at this point long extension 18 is parallel to short section 30 as
20 shown by the dotted lines. At some point, either before or after being brought next to each other,
21 long extension 18 is bent over forming a connection locking slot 22 that covers some portion of
22 the back face 32 of short extension 14. In a preferred embodiment, the front face 30 of long

1 extension 18 covers approximately one-half of the back face 32 of short extension 14 when the two
2 unjoined edges are brought together and short extension 14 is captured within connection locking
3 slot 22.

4 The method of forming reinforcing ridge 10 in a preferred embodiment requires the
5 positioning of first unjoined edge 16 adjacent to second unjoined edge 20 so that the front face 30
6 of long extension 18 meets with the front face 30 of short extension 14. In regard to forming,
7 Applicant's invention enables rolled/machine forming of reinforcing ridge 10, so that no additional
8 handling, crimping or the like is required to securely join the unjoined edges. At that point, long
9 extension 18 is bent over short extension 14, forming connection locking slot 22, and resulting in
10 reinforcing ridge 10. Obviously, connection locking slot 22 may be formed before bringing long
11 extension 18 next to short extension 14. Other preferred methods include forming at least one
12 reinforcing rib 26 in side 27 opposite the reinforcing ridge 10. Still further preferred methods
13 include forming strength indents 28 in the sides, 23 and 25, adjacent to reinforcing ridge 10.

14 As is obvious to those of ordinary skill in the art, once reinforcing ridge 10 is created,
15 multiple sections of rigid material 12 may be joined together using automatic joining devices as
16 previously discussed. This alone greatly reduces the cost of structures made of man-made
17 materials. The addition of reinforcing ribs 26 and/or strength indents 28 further increase the
18 usability and versatility and affordability of structures made from man-made materials.

19 While the present invention has been disclosed in connection with the preferred
20 embodiments thereof, it should be understood that there may be other embodiments which fall
21 within the spirit and scope of the invention as defined by the following claims.
22

1 Claims:

2

3 1. In a length of rigid material with first and second unjoined edges, a reinforcing ridge

4 comprising:

- 5 (a) a short extension connected to said first unjoined edge;
- 6 (b) a long extension connected to said second unjoined edge; and
- 7 (c) a connection locking slot in said long extension conformed to just receive and retain
- 8 said short section when said unjoined edges are brought together.

9

10 2. The invention of Claim 1 further comprising:

- 11 (a) front and back faces on said short and long extensions; and
- 12 (b) said long extension front face conformed to generally cover said short extension
- 13 front face and partially cover said short extension back face.

14

15 3. The invention of Claim 2 wherein said long extension is approximately twice as long as

16 said short section and said long extension generally covers all of the front face of said short

17 extension and approximately one-half of the back face of said short extension.

18

19 4. The invention of Claim 1 wherein said rigid material forms a rectangle with said

20 reinforcing ridge in one side and at least one reinforcing rib in a side facing said

21 reinforcing ridge.

- 1 5. The invention of Claim 4 further comprising two reinforcing ribs.
- 2
- 3 6. The invention of Claim 1 wherein said rigid material forms a rectangle with said
- 4 reinforcing ridge in one side and at least one reinforcing rib in a side facing said
- 5 reinforcing ridge and at least one strength indent in a side adjacent to said reinforcing
- 6 ridge.
- 7
- 8 7. The invention of Claim 6 further comprising two strength indents, one strength indent in
- 9 each side adjacent to said reinforcing ridge.
- 10
- 11 8. The invention of Claim 6 further comprising a pair of strength indents, two strength
- 12 indents in each side adjacent to said reinforcing ridge.
- 13
- 14 9. The invention of Claim 6 further comprising a pair of reinforcing ribs in a side facing said
- 15 reinforcing ridge.
- 16
- 17 10. The invention of Claim 6 further comprising a pair of reinforcing ribs in a side facing said
- 18 reinforcing ridge and a pair of strength indents, one strength indent in each side adjacent
- 19 to said reinforcing ridge.
- 20

1 11. The invention of Claim 6 further comprising a pair of reinforcing ribs in a side facing said
2 reinforcing ridge and two pairs of strength indents, one pair of strength indents in each side
3 adjacent to said reinforcing ridge.

4
5 12. The invention of Claim 1 wherein said rigid material is sheet metal.

6
7 13. In a length of rigid material with first and second unjoined edges, a method of joining said
8 edges and forming a reinforcing ridge comprising the steps of:

- 9 (a) forming a short extension in said first unjoined edge;
10 (b) forming a long extension in said second unjoined edge; and
11 (c) bringing said first and second unjoined edges together and bending said long
12 extension over said short extension and forming a connection locking slot so that
13 said first and second unjoined edges are joined together and form said reinforcing
14 ridge.

15
16 14. The method of Claim 13 further comprising the steps of forming said short and long
17 extensions with front and back faces so that when said unjoined edges are joined together,
18 and the front face of said long extension generally covers the front face of said short
19 extension and partially covers the back face of said short extension.

20
21 15. The method of Claim 14 further comprising the step of forming said long extension so that
22 it is approximately twice as long as said short extension and generally covers the front face

1 of said short extension and approximately one-half of the back face of said short extension
2 when said unjoined edges are brought together.
3

4 16. The method of Claim 13 further comprising the steps of:

5 (a) forming said rigid material into a rectangular shape with said reinforcing ridge in
6 one side; and

7 (b) forming at least one reinforcing rib in a side facing said reinforcing ridge.
8

9 17. The method of Claim 16 further comprising the step of forming two reinforcing ribs in the
10 side facing said reinforcing ridge.

11
12 18. The method of Claim 16 further comprising the step of forming at least one strength indent
13 in a side adjacent to said reinforcing ridge.

14
15 19. The method of Claim 18 further comprising the step of forming a pair of strength indents,
16 one in each side adjacent to said reinforcing ridge.

17
18 20. The method of Claim 18 further comprising the step of forming two pairs of strength
19 indents, one pair in each side adjacent to said reinforcing ridge.
20

REINFORCING RIDGE APPARATUS AND METHOD

ABSTRACT OF THE DISCLOSURE

In a length of rigid material (12) with first and second unjoined edges (16 and 20), a reinforcing ridge (10) includes a short extension (14) connected to the first unjoined edge (16). A long extension (18) is connected to the second unjoined edge (20). When the unjoined edges (16 and 20) are brought together, the long extension (18) is bent over the short extension (14) forming a connection locking slot (22) and the reinforcing ridge (10). In a preferred embodiment, at least one reinforcing rib (26) is formed in a side opposite the reinforcing ridge (10) and at least one strength indent (28) is formed in a side adjacent to the reinforcing ridge (10). As formed, the rigid material is sufficiently strong to resist collapse when joined together by use of automatic joining devices.

\\C:\db\le-h\Hemming2\100\DraftApp1.wpd

COMBINED DECLARATION AND POWER OF ATTORNEY

As the below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: REINFORCING RIDGE APPARATUS AND METHOD described and claimed in the attached specification;

I have reviewed and understand the content of the attached specification, including the claims, as amended by any amendment referred to above. I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application in accordance with Title 37, C.F.R. §1.56(a).

I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:


John Nevin Shaffer, Jr., Reg. No. 29,858
Russell D. Culbertson, Reg. No. 32,124
Rafael V. Baca, Reg. No. 44,016

Address telephone calls to J. Nevin Shaffer, Jr. at telephone number: 512/327-8932. Address correspondence to:
J. Nevin Shaffer, Jr., 1250 Capital of Texas Highway, S., Building One, Suite 360, Austin, Texas 78746.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

* * * * *

25 SEP '00
Date


Gustav M. Stromback

Residence:	Austin, Texas
Citizenship:	United States of America
Post Office Address:	9019 Balcones Club Drive, Austin, Texas 78750